

What Is Claimed:

1. A circuit interrupting device having a mounting strap, the circuit interrupting device comprising:
 - 5 a support member adapted to be coupled to the mounting strap and receive a trunnion; and
 - a button having trunnion means adapted to be received by the support member.
2. The device of claim 1 wherein the support member comprises a protruding member adapted to be received by an opening in the mounting strap for locating the
 - 10 support member on the mounting strap..
3. The device of claim 2 wherein the protruding member is a dowel.
4. The device of claim 3 wherein the support member comprises legs adapted to engage side edges of the mounting strap.
5. The device of claim 4 wherein the legs of the support member have hooks
 - 15 for engaging side edges of the mounting strap.
6. The device of claim 5 wherein the hooks are adapted to bend around and engage the side edges of the mounting strap as the support member is being positioned on the mounting strap .
7. The device of claim 5 wherein the support member comprises first and
 - 20 second projections having aligned openings which function as bearings for receiving the trunnion of the button.
- 8.— The device of claim 7 wherein the trunnion can be snapped into the aligned openings.
9. The device of claim 8 further comprising a spring coupled to urge the
 - 25 button to rotate away from the mounting strap.
10. The device of claim 9 wherein the spring is positioned between the button and the mounting strap.
11. The device of claim 5 wherein the support member is pivotally coupled to the button.

12. A circuit interrupting device having a mounting strap, the circuit interrupting device comprising:

a support member having trunnion means; and

a button having a void for pivotally engaging the trunnion means of the support
5 member.